

Abmessungen Endkappen

Bezeichnung	bei Lieferung		nach Schrumpfung	empfohlener Anwendungsbereich
	Durchmesser - H (min.)	Länge - L (min.)	Durchmesser (max.)	
	mm	mm	mm	mm
E 6 / 2	6	25	2	2.2 - 5.5
E 8 / 2	8	25	2	2.2 - 7.2
E 12 / 3	12	38	3	4.0 - 10.0
E 12 / 4	12	38	4	5.0 - 10.0
E 14 / 4	14	40	4	5.0 - 12.0
E 14 / 4	14	60	4	5.0 - 12.0
E 15 / 4	15	42	4	5.0 - 13.5
E 20 / 6	20	55	6	6.6 - 18.0
E 20 / 8	20	65	8	9.0 - 18.0
E 22 / 8	22	65	8	9.0 - 20.0
E 24 / 8	24	65	8	9.0 - 22.0
E 26 / 11	26	75	11	12.0 - 23.0
E 35 / 15	35	85	15	17.0 - 31.0
E 35 / 15	35	100	15	17.0 - 31.0
E 42 / 15	42	85	15	17.0 - 38.0
E 42 / 15	42	105	15	17.0 - 38.0
E 55 / 25	55	130	25	27.0 - 49.0
E 55 / 25	55	145	25	27.0 - 49.0
E 55 / 25	55	165	25	27.0 - 49.0
E 62 / 25	62	165	25	28.0 - 56.0
E 75 / 26	75	160	26	29.0 - 67.0
E 75 / 30	75	160	30	33.0 - 67.0
E 75 / 32	75	170	32	35.0 - 67.0
E 75 / 36	75	120	36	37.0 - 67.0
E 105 / 45	105	160	45	49.0 - 94.0
E 120 / 60	120	160	60	66.0 - 108.0
E 145 / 60	145	160	60	66.0 - 130.0
E 160 / 82	160	160	82	90.0 - 144.0
E 200 / 90	200	160	90	99.0 - 180.0
E 230 / 125	230	220	125	140.0 - 200.0
E 310 / 120	310	220	120	140.0 - 280.0
E 400 / 204	400	220	204	230.0 - 380.0
E 500 / 200	500	220	200	230.0 - 480.0
Lange Ausführung				
E 42 / 15	42	190	15	17.0 - 38.0
E 62 / 22	62	190	22	24.0 - 56.0
E 75 / 34	75	190	34	37.0 - 67.0

weitere Abmessungen auf Anfrage

